

A flexible solution to the permanent or temporary containment of liquids.

## Applications



- Oil spill clean up/decontamination pool
- Laboratory test tank / mixing tank
- Fire services
- Temporary liquid storage
- Farming - aquaculture

Supplied in an easy carry bag



## Benefits



- Simple assembly, no tools required
- Suitable for a wide range of climates
- Corrosion resistant
- Multi-purpose use
- Easy to clean
- Adapts to uneven ground
- Easy to transport

EzeeBOX™ Add-On available



## Specification

FASTANK	• 1	3	5
Assembled	1.2 dia x 0.9m h 47 dia x 35" h	1.8 dia x 1.25m h 70 dia x 35" h	2.3 dia x 1.25m h 90 dia x 50" h
Packaged	0.92 x 0.3 x 0.23m h 36x 12 x 9" h	1.26 x 0.28 x 0.33m h 49 x 11 x 13" h	1.26 x 0.28 x 0.33m h 49 x 11 x 13" h
Weight	11 kg 25 lbs	28 kg 60 lbs	36 kg 80 lbs
Capacity	1000 Litres 220 Imp Gls 260 US Gal	3000 Litres 660 Imp Gls 800 US Gal	5000 Litres 1100 Imp Gls 1320 US Gal

Manufactured to ISO 9001 2008 Quality standard from (900gsm) rip stop acrylic and vinyl coated polyester fabric.

Structural aluminium frame with glass nylon filled joints.

Temp Range -20°C to +80°C.  
UV Resistant.

Add-Ons Available:

- Ground Mat
- Hand Pump
- Roof Cover
- Polythene liner
- Decanting valve, Pipe Kit
- Pipe Saddle, Foot Plates
- Tap Stand, Ezeebox

Please see overleaf>>





### Ground Mat

- Provides extra protection on rough or sharp ground
- Made from heavy duty vinyl coated reinforced fabric
- Can be used to provide an additional washable work area

### Hand Pump

- Output 110L/min
- Attaches easily to tank
- Includes 2m of suction hose & 5m of 38mm dia outlet hose



### Roof cover

- Reduces evaporation, and prevents contamination
- Can be reversed for use as a rainwater catcher

### Polythene liner

- Virgin food grade polythene
- Prevents cross contamination
- Minimises cleaning of tank after use



### Decanting valve

- Oil / water separation; enables reduction in the volume of stored liquid, thus reduced disposal & transport cost
- Adjustable flow rate
- Drain Valve

### Pipe Kit

- Connects to reinforced wall
- Provide inlet, outlet, overflow and aeration options





### Pipe Saddle

- 75mm (3") or 50mm (2")
- Simple to attach - no tools
- Safely pump over tank wall

### Foot plates

- For use on soft ground
- Easily attached, no tools
- Size 133mm<sup>2</sup> (5") square



### FASTAP® Tapstand

- Distribution of drinking water during emergencies
- 6 flexible outlets
- Factory tested, no leaks
- UK Patent No. GB2499726

### EzeeBOX®

- Robust weatherproof storage container for **FASTANK**
- Multipurpose use on site

